

Model No. **PLTBPOWINSBLK** Compact Power Insert (Power Module)

Compact, fire-retardant power solution featuring dual UL outlets, USB-C PD (30W), USB 3.0, and HDMI connectivity. Designed for integrated table use with fast charging and built-in protection against overcurrent, overheating, and voltage fluctuations. Includes 2.45m power cable.



Features

- Dual UL power outlets + additional bottom outlet
- USB-C Power Delivery (30W fast charging)
- USB 3.0 port + HDMI connectivity
- Supports multiple fast-charging protocols
- Built-in safety: overcurrent, overvoltage, overheating, short circuit protection
- Fire-retardant construction
- Compact, integrated design for table applications
- 2.45m power cable with UL plug
- Rated 125V / 15A

Material	Fire retardant plastic
Product Size	179w x 68d x 80.1h mm
Modules	2 UL power socket + 1 UL power socket (bottom), 1 PD30W charger, 1 (HDMI + USB3.0) female-to-female couplers
Power Cable	2.45 meter with UL plug (AWG14)
Rated Voltage	AC125Vac
Rated Current	15A
30W Power Delivery charger	<p>Output</p> <p>Port C1 or C2: 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A (30W max.) Port C1 + C2: 5V/3A (15W max.)</p> <p>Fast charging protocols</p> <p>PD2.0, PD3.0 PPS, QC2.0, QC3.0, QC4.0, QC4+, HSCP, FCP, AFC, BC1.2,</p> <p>Short circuit protection</p> <p>Over current protection</p> <p>Over temperature protection</p> <p>Over voltage protection</p>
Withstanding Voltage	DC3000V10mA 10S
Working Temperature	0°C - 60° C (32° F - 140° F)

*Available colors may vary